



# AlfaNova 400

## Fusion-bonded plate heat exchanger

### General information

AlfaNova is a plate heat exchanger made of 100% stainless steel. It is based on Alfa Laval's revolutionary technology, AlfaFusion, the art of joining stainless steel components together.

AlfaNova heat exchangers are well suited in applications which put high demand on cleanliness, applications where ammonia is used or applications where copper or nickel contamination is not accepted. Its high resistance to corrosion makes it both hygienic and environmental friendly.

It is extremely compact compared to its capacity to withstand great strains in demanding heat transfer applications.

### Applications

- Evaporating
- Economizing
- Absorption systems
- Process cooling/heating
- Oil cooling

### Working principles

The heating surface consists of thin corrugated metal plates stacked on top of each other. Channels are formed between the plates and corner ports are arranged so that the two media flow through alternate channels, always in countercurrent flow. The media are kept in the unit by a bonded seal around the edge of the plates. The contact points of the plates are also bonded to withstand the pressure of the media handled.

### Standard design

The plate pack is covered by cover plates. Connections are located in the front or rear cover plate. The channel plates are corrugated to improve heat transfer design.


### Particulars required for quotation

To enable Alfa Laval's representative to make a specific quotation, enquiries should be accompanied by the following particulars:

- Flow rates or heat load required
- Temperature program
- Physical properties of liquids in question
- Desired working pressure
- Maximum permitted pressure drop



### Examples of connections




Compact flanges



Welding



Clamp




Soldering




Outside threaded


**AlfaNova 400 – PED approval pressure/temperature graph 1)**




**AlfaNova 400 – ASME approval pressure/temperature graph 2)**



**AlfaNova 400 – KHK approval pressure/temperature graph**



**AlfaNova 400 – CRN approval pressure/temperature graph**



**Standard data**

Min. working temperature	see graph
Max. working temperature	see graph
Min. working pressure	vacuum
Max. working pressure	see graph
Volume per channel, litres (ga)	0.74 (0.19)
Max. particle size mm (inch)	1.8 (0.07)
Max. flowrate* m <sup>3</sup> /h (gpm)	200 (880)
Min. nbr of plates	10
Max. nbr of plates	270


\*) Water at 5 m/s (16.4 ft/s) (connection velocity)

**Standard materials**

Cover plates	Stainless steel
Connections	Stainless steel
Plates	Stainless steel
AlfaFusion filler	Stainless steel

**Standard dimensions \***

A measure mm	=	14 + (2.65 * n) ±10 mm
A measure inch	=	0.55 + (0.1 * n) ±0.39 inch
Weight kg	=	22 + (1.4 * n)
Weight lb	=	48.5 + (3.09 * n)



For exact values please contact your local Alfa Laval representative.

**How to contact Alfa Laval**

Up-to-date AlfaLaval contact details for all countries are always available on our website on [www.alfalaval.com](http://www.alfalaval.com)