

SAFETY DATA SHEET

in accordance with REACH (1907/2006/EC, as amended by 453/2010/EC)

Revision date: 21 June 2013 **Initial date of issue:** 2 May 2007 **SDS No.** 235A-12

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

ARC 858 (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY
860 Salem Street
Groveland, MA 01834-1507, USA
Tel.: +1 978-469-6446 Fax: +1 978-469-6785
(Mon. - Fri. 8:30 - 5:00 PM EST)
E-mail (SDS questions): ProductMSDSs@chesterton.com
E-mail: customer.service@chesterton.com
SDS requests: www.chesterton.com

Supplier:

1.4. Emergency telephone number

24 hours per day, 7 days per week
Call Infotrac: 1-800-535-5053
Outside N. America: +1 352-323-3500 (collect)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / GHS

Eye Irrit. 2, H319
Skin Irrit. 2, H315
Skin Sens. 1, H317
Aquatic Chronic 2, H411

2.1.2. Classification according to Directive 1999/45/EC

Irritant; Xi; R36/38
R43
Dangerous for the environment; N; R51/53

2.1.3. Canadian WHMIS classification

D2A: Very toxic materials causing other effects; D2B: Toxic materials causing other effects

2.1.4. Australian classification

Hazardous according to criteria of Safe Work Australia.

2.1.5. Additional information

For full text of H-statements and R-phrases: see SECTIONS 2.2 and 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP] / GHS

Hazard pictograms:



Signal word:

Warning

Hazard statements:	H319	Causes serious eye irritation.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary statements:	P273	Avoid release to the environment.
	P280	Wear protective gloves and eye/face protection.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P337/313	If eye irritation persists: Get medical advice/attention.
	P363	Wash contaminated clothing before reuse.
	P391	Collect spillage.
Supplemental information:	None	

2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	Classification (acc. to 1272/2008/EC)	Classification (67/548/EEC)
Epoxy resin (number average molecular weight <= 700)	30-50	25068-38-6 500-033-5	01-211945 6619-26	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Xi; R36/38 R43 N; R51/53
Silicon Carbide	15-25	409-21-2 206-991-8	NA	Not classified*	Not classified
Titanium dioxide	1-5	13463-67-7 236-675-5	01-211948 9379-17	Not classified*	Not classified

Indications of danger acc. to 67/548/EEC: Xi: Irritant; N: Dangerous for the environment

*Substance with a workplace exposure limit.

For full text of H-statements and R-phrases: see SECTION 16.

¹Classified according to: * 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F), California Proposition 65
* 1272/2008/EC, 67/548/EEC, 99/45/EC, REACH
* Controlled Products Regulations
* Safe Work Australia [NOHSC: 1008 (2004)]

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if you feel unwell.
Skin contact:	Remove contaminated clothing. Wash clothing before reuse. Wash skin with soap and water. Consult physician.
Eye contact:	Flush eyes for at least 15 minutes with large amounts of water. Contact physician if irritation persists.
Ingestion:	Do not induce vomiting. Contact physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Moderate eye and skin irritant. May cause skin sensitization as evidence by rashes or hives.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: FIRE-FIGHTING MEASURES**5.1. Extinguishing media**

Suitable extinguishing media: Carbon Dioxide, dry chemical, foam or water fog

Unsuitable extinguishing media: None known

5.2. Special hazards arising from the substance or mixture

Container may rupture from gas generation when exposed to intense heat.

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

Flammability Classification: –

HAZCHEM Emergency Action Code: 2 **Z**

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Scoop up and transfer to a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Utilize exposure controls and personal protection as specified in Section 8. Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated leather including shoes cannot be decontaminated and should be discarded. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry area.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL		ACGIH TLV		UK WEL ²		AUSTRALIA ES ³	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Epoxy resin (number average molecular weight <= 700)	–	–	–	–	–	–	–	–
Silicon Carbide	(total)	15	(total)	10	(total)	10	–	10
	(resp)	5	(resp)	3	(resp)	4		
Titanium dioxide	–	15	–	10	(total)	10	–	10
					(resp)	4		

² EH40 Workplace exposure limits, as amended.

³ Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

8.2. Exposure controls**8.2.1. Engineering measures**

No special requirements. If exposure limits are exceeded, provide adequate ventilation. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If product is sprayed, utilize an approved air-supplied respirator.

Protective gloves: Chemical resistant gloves (e.g., nitrile rubber, butyl rubber, neoprene, PVC)

Eye and face protection: Safety glasses

Other: Impervious clothing as necessary to prevent skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	paste	Odour	sweet odor
Colour	white	Odour threshold	not determined
Initial boiling point	not applicable	Vapour pressure @ 20°C	not determined
Melting point	not determined	% Aromatics by weight	0%
% Volatile (by volume)	< 1%	pH	not applicable
Flash point	> 249°C (> 480°F)	Relative density	1.6 kg/l
Method	PM Closed Cup	Weight per volume	13.5 lbs/gal.
Viscosity	not determined	Coefficient (water/oil)	< 1
Autoignition temperature	not determined	Vapour density (air=1)	> 1
Decomposition temperature	no data available	Rate of evaporation (ether=1)	< 1
Upper/lower flammability or explosive limits	not determined	Solubility in water	Insoluble
Flammability (solid, gas)	not applicable	Oxidising properties	not applicable
Explosive properties	not applicable		

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Temperatures above 300°C (572°F).

10.5. Incompatible materials

Strong mineral acids and bases, strong organic bases and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, aldehydes, acids and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Primary route of exposure under normal use: Skin and eye contact. Personnel with pre-existing skin and eye disorders and skin allergies may be aggravated by exposure.

Acute toxicity -**Oral:**

Substance	Test	Result
Epoxy resin	LD50, rat	> 2000 mg/kg
Titanium dioxide	LD50, rat	> 10000 mg/kg

Dermal:

Substance	Test	Result
Epoxy resin	LD50, rabbit	> 2000 mg/kg
Titanium dioxide	LD50, rabbit	> 10000 mg/kg

Inhalation:

Substance	Test	Result
Epoxy resin	LC0, rat, 5-8 h	No mortality at vapor saturation level
Titanium dioxide	LC50, rat, 4 h	> 6.82 mg/l

Skin corrosion/irritation: Causes skin irritation.

Substance	Test	Result
Epoxy resin	Skin irritation, rabbit	Moderate irritation
Titanium dioxide	Skin irritation, rabbit	Not irritating

Serious eye damage/irritation: Causes serious eye irritation.

Substance	Test	Result
Epoxy resin	Eye irritation, rabbit	Moderate irritation
Titanium dioxide	Eye irritation, rabbit	Not irritating

Respiratory or skin sensitisation: May cause an allergic skin reaction.

Substance	Test	Result
Epoxy resin	Skin sensitization, guinea pig	Sensitizing
Titanium dioxide	Skin sensitization, guinea pig	Not sensitizing

Germ cell mutagenicity: Epoxy resin, Silicon Carbide, Titanium dioxide: based on available data, the classification criteria are not met.

Carcinogenicity: The International Agency for Research on Cancer (IARC) has designated inhaled titanium dioxide as possibly carcinogenic to humans (group 2B). The titanium dioxide in this product does not separate from the mixture or in of itself become air-borne, therefore it does not present a hazard in normal use. Epoxy resin: based on available data, the classification criteria are not met.

Reproductive toxicity: Epoxy resin, Silicon Carbide, Titanium dioxide: based on available data, the classification criteria are not met.

STOT-single exposure: Epoxy resin, Silicon Carbide, Titanium dioxide: based on available data, the classification criteria are not met.

STOT-repeated exposure: Epoxy resin, Silicon Carbide, Titanium dioxide: based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Epoxy resin (number average molecular weight ≤ 700) is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Unreacted components (Parts A and B), improperly released to the environment, can cause ground and water pollution. Epoxy resin (number average molecular weight ≤ 700): not readily biodegradable (5% biodegradation, OECD 301F, 28 days).

12.3. Bioaccumulative potential

Epoxy resin (number average molecular weight ≤ 700): bioconcentration factor = 31 (QSAR), low potential for bioaccumulation.

12.4. Mobility in soil

Insoluble in water. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Epoxy resin (number average molecular weight ≤ 700): if product enters soil, it will be mobile and may contaminate groundwater (log Koc ≤ 3.65).

12.5. Results of PBT and vPvB assessment

Not available

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Combine resin and curative. The final cured material is considered nonhazardous. Unreacted components are a special waste (classified as hazardous according to 2008/98/EC). May be incinerated at an appropriate facility. Check local, state and national/federal regulations and comply with the most stringent requirement.

European List of Wastes code: 08 04 09

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

ADR/RID/ADN/IMDG/ICAO: UN3082

TDG: UN3082

US DOT: UN3082

14.2. UN proper shipping name

ADR/RID/ADN/IMDG/ICAO: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

TDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

US DOT: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es)

ADR/RID/ADN/IMDG/ICAO: 9

TDG: 9

US DOT: 9

14.4. Packing group

ADR/RID/ADN/IMDG/ICAO: III

TDG: III

US DOT: III

14.5. Environmental hazards

MARINE POLLUTANT

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

NOT APPLICABLE

14.8. Other information

US DOT: ERG NO.171, May be shipped as Limited Quantities in packaging having a rated capacity gross weight of 66 lb. or less and in inner packages not over 5 Liters (49 CFR 173.155 (b,2))

IMDG: EmS. F-A, S-F

ADR: Classification code M6 Tunnel restriction code (E)

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 94/33/EC on the protection of young people at work.

15.1.2. National regulations**US EPA SARA TITLE III**

312 Hazards: 313 Chemicals:

Immediate None

Delayed

Hazardous Materials Identification System (HMIS)

4 = Severe Hazard
3 = Serious Hazard
2 = Moderate Hazard
1 = Slight Hazard
0 = Minimal Hazard
* = See Section 8

HEALTH	1
FLAMMABILITY	1
REACTIVITY	1
Personal Protection	*

JAPAN PRTR

Class I Chemicals:

None

Class II Chemicals:

None

Other national regulations: National implementation of the EC Directive referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ACGIH: American Conference of Governmental Industrial Hygienists
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE: Acute Toxicity Estimate
 BCF: Bioconcentration Factor
 CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
 ES: Exposure Standard
 GHS: Globally Harmonized System
 ICAO: International Civil Aviation Organization
 IMDG: International Maritime Dangerous Goods
 LC50: Lethal Concentration to 50 % of a test population
 LD50: Lethal Dose to 50% of a test population
 LOEL: Lowest Observed Effect Level
 N/A: Not Applicable
 NA: Not Available
 NOAEL: No Observed Adverse Effect Level
 NOEL: No Observed Effect Level
 OSHA: Occupational Health & Safety Administration
 PBT: Persistent, Bioaccumulative and Toxic substance
 PEL: Permissible Exposure Limit
 (Q)SAR: Quantitative Structure-Activity Relationship
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 STOT: Specific Target Organ Toxicity
 TDG: Transportation of Dangerous Goods (Canada)
 TLV: Threshold Limit Value
 US DOT: United States Department of Transportation
 vPvB: very Persistent and very Bioaccumulative substance
 WEL: Workplace Exposure Limit
 WHMIS: Workplace Hazardous Materials Information System
 Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission de la santé et de la sécurité du travail (CSST)
 European chemical Substances Information System (ESIS)
 European Chemicals Agency (ECHA) - Information on Chemicals
 Hazardous Substances Data Bank (HSDB)
 Hazardous Substances Information System (HSIS)
 Swedish Chemicals Agency (KEMI)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008:

Classification	Classification procedure
Eye Irrit. 2, H319	Calculation method
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1, H317	Bridging principle "Dilution"
Aquatic Chronic 2, H411	Calculation method

Relevant H-statements: H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H411: Toxic to aquatic life with long lasting effects.

Relevant R-phrases: R36/38: Irritating to eyes and skin.
 R43: May cause sensitisation by skin contact.
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard pictogram names: Exclamation mark, environment

Changes to the SDS in this revision: Sections 2, 3, 4, 5, 8, 10, 11, 12, 13, 15.1, 16.

Further information: None

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.