

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Commercial product name: ELASTOSIL® E43
TRANSPARENT****1.2 Relevant identified uses of the substance or mixture and uses advised against**Use of substance / preparation:
Industrial.
Adhesive / sealant .**1.3 Details of the supplier of the safety data sheet****Manufacturer:** Wacker Chemie AG
Street/POB-No.: Hanns-Seidel-Platz 4
State/postal code/city: D 81737 München
Telephone: +49 89 6279-0
Telefax: +49 89 6279-1770**Distributor:** Wacker Chemie AG
Care of Wacker Chemicals Australia Pty Ltd
Street/POB-No.: Unit 1 / 35 Dunlop Road
State/postal code/city: Mulgrave, Victoria 3170
Telephone: +61 3 9541 8900
Telefax: +61 3 9541 8989**Information about the Safety Data Sheet:** **Telephone** +49 8677 83-4888
Telefax +49 8677 886-9722
eMail WLCP-MSDS@wacker.com**1.4 Emergency telephone number****Emergency Information:** **Regulatory Compliance Manager** **+61 3 9541 8900**
Emergency response service only (24h): **+61 2 8014 4558****SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**Non-Hazardous Chemical according to Australian GHS criteria. Non-Dangerous Goods to the ADG Code.
Not a hazardous substance or mixture.**2.2 Label elements**

No labeling according to GHS required.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

not applicable

3.2 Mixtures**3.2.1 Chemical characteristics**

Polydimethylsiloxane and fillers and auxiliaries and acetoxysilane cross-linker

3.2.2 Ingredients

Type	CAS No.	Substance	Content %
INHA	4253-34-3	Triacetoxymethylsilane	<5

Type: INHA: ingredient, VERU: impurity

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wipe off excess material with cloth or paper. Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Material cannot be inhaled under normal conditions.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Advice for the doctor:

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

alcohol-resistant foam , carbon dioxide , water mist , sprinkler system , sand , extinguishing powder .

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Precautions for safe handling:**

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities**Conditions for storage rooms and vessels:**

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C**7.3 Specific end use(s)**

No data available.

7.4 Regulations and standards (Australia):

Store and handle in accordance with Work Health & Safety Regulations or Occupational Health & Safety Regulations.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Maximum airborne concentrations at the workplace:**

CAS No.	Substance	Type	mg/m ³	ppm	Dust fract.	Fibre/m ³
64-19-7	Acetic acid	ES_AU	25.0	10.0		
71-23-8	1-Propanol	ES_AU	500.0	200.0		
	Tin compounds (organic)	ES_AU	0.1			

Tin compounds (organic): short time exposure limit is 0.2 mg/m³. Reference: American Conference of Governmental Industrial Hygienists (ACGIH), Documentation of Threshold Limit Values and Biological Exposure Indices, 6th Edition, ACGIH, Cincinnati, Ohio, 1991

8.2 Exposure controls**8.2.1 Exposure in the work place limited and controlled****General protection and hygiene measures:**

Observe standard industrial hygiene practices for the handling of chemical substances. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Avoid contact with eyes and skin. Preventive skin protection recommended. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Provide emergency shower and eye-bath. Do not eat, drink or smoke when handling.

Personal protection equipment:**Respiratory protection**

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

protective goggles .

Hand protection

Gloves are required at all times when handling the material.

Recommended glove types: Protective gloves made of butyl rubber
thickness of the material: > 0.3 mm
Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of nitrile rubber
thickness of the material: > 0.1 mm
Breakthrough time: 60 - 120 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

protective clothing .

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.2.3 Specific notes (Australia):

Select and use respirators in accordance with AS1715/1716.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Property:	Value:	Method:
Appearance		
Physical state	liquid	
Form	paste	
Colour	colourless	
Odour		
Odour	pungent	
Odour limit		
Odour limit	no data available	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not applicable	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point	not applicable	
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

Upper explosion limit (UEL).....	not applicable	
Vapour pressure		
Vapour pressure.....	not applicable	
Solubility(ies)		
Water solubility / miscibility.....	virtually insoluble	
Vapour density		
Relative gas/vapour density	No data known.	
Relative Density		
Relative Density	1.09 (20 °C)	(DIN 53217)
	(Water / 4 °C = 1,00)	
Density	1.09 g/cm ³ (20 °C)	(DIN 53217)
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water.....	No data known.	
Auto-ignition temperature		
Ignition temperature	ca. 460 °C	(-)
Decomposition temperature		
Thermal decomposition.....	No decomposition when used according to regulations.	
Viscosity		
Viscosity (dynamic)	300000 mPa.s at 25 °C	(DIN EN ISO 2555)
Molecular mass		
Molecular mass	not applicable	

9.2 Other information

Solubility in water: Hydrolytic decomposition occurs. pH Value: Product displays acidic reaction with water.
Explosion limits for released acetic acid: 4 - 17%(V).

SECTION 10: Stability and reactivity**10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

moisture , Heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with: water , basic substances and alcohols . Reaction causes the formation of: acetic acid .

10.6 Hazardous decomposition products

By hydrolysis: acetic acid . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****11.1.1 Acute toxicity****Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2009 mg/kg	Rabbit	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

Product details:

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	in vitro assay; Bovine eye / bovine cornea	Conclusion by analogy OECD 437
not irritating	Rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Further toxicological information

In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

SECTION 12: Ecological information**12.1 Toxicity****Assessment:**

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

Product details:

Result/Effect	Species/Test system	Source
ErC50: > 100 mg/l (measured)	static Desmodesmus subspicatus (72 h)	Conclusion by analogy OECD 201

12.2 Persistence and degradability**Assessment:**

Silicone content: biologically not degradable. Separation by sedimentation. The product of hydrolysis (acetic acid) is readily biodegradable.

12.3 Bioaccumulative potential**Assessment:**

Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil**Assessment:**

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

12.7 Additional information

In cross-linked state not soluble in water. Easily separable from water by filtration.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****13.1.1 Material****Recommendation:**

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging**Recommendation:**

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information**14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group****Land transport ADG Code (road and rail):**

Valuation: Not regulated for transport

Transport by sea IMDG-Code:

Valuation: Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation: Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.1.1 Poisons Standard (Standard for the Uniform Scheduling of Medicines and Poisons; SUSMP)**Poisons Schedule number:**

Not a Scheduled Poison.

Label elements:**15.2 Details of international registration status**

Relevant information about individual substance inventories, where available, is given below.

Japan	ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	AICS (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.
China.....	IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan	TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea)	AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by the latter.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 4.3 (AU)

Date of print: 24.08.2020

Date of last alteration: 18.11.2019

SECTION 16: Other information**16.1 Material**

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

16.3 Glossary of Terms:

CAS No. - Chemical Abstracts Service Registry Number

UN No. - United Nations Dangerous Goods Number

ADG Code - Australian Dangerous Goods Code for the Transport of Dangerous Goods by Road & Rail

IMDG Code - International Maritime Dangerous Goods Code

IATA Regs - International Air Transport Association (IATA) Dangerous Goods Regulations

NOHSC - Australian National Occupational Health and Safety Commission (Note: NOHSC documents are now published by Safe Work Australia)

OEL - Occupational exposure limit in Great Britain

AGW - Occupational exposure limit in Germany

ES_AU - Occupational exposure standard in Australia

- End of Safety Data Sheet -