

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

1. Identification

1.1 Identification of the substance or preparation:

Commercial product name: ELASTOSIL® E43
TRANSPARENTUse of substance / preparation: Industrial.
Adhesive / sealant .

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemie AG
Hanns-Seidel-Platz 4
81737 München
Germany**Customer information:** Wacker Chemical Corporation
3301 Sutton Road
Adrian, Michigan 49221-9397
USA
InfoLine:
Tel (517) 264-8240, Fax (517) 264-8740
Hours of operation:
Monday - Friday, 8 am to 5 pm (eastern standard time)
Corporate website: www.wacker.com**Emergency telephone no. (24h):** +1 646 844 7309

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazard identification

2.1 Classification of the substance or mixture

Classification (GHS):

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (GHS):

No labeling according to GHS required.

2.3 Other hazards

No data available.

3. Composition/Information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane and fillers and auxiliaries and acetoxysilane cross-linker

3.2 Information on ingredients:

Type	CAS No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	4253-34-3	Triacetoxymethylsilane		<5.0	

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

4.2 After inhalation

If inhaled, remove to fresh air.

4.3 After contact with the skin

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

If swallowed, do not induce vomiting. Induce drinking plenty of water in small portions. Get medical attention immediately. Show label.

5. Fire-fighting measures

5.1 Fire and explosion hazards:

Consider possible formation of explosive mixtures with air, for example in uncleaned containers.

5.2 Recommended extinguishing media:

water-spray , carbon dioxide , dry chemical or alcohol-resistant foam .

5.3 Unsuitable extinguishing media:

sharp water jet

5.4 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide , acetic acid and incompletely burnt hydrocarbons .

5.5 Fire fighting procedures:

Cool endangered containers with water. Fire fighters should wear full protective clothing including a self-contained breathing apparatus.

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods for cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

6.4 Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

7. Handling and storage

7.1 Handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C (32 °F)

8. Exposure controls/Personal protection

8.1 Engineering controls

Ventilation:

Use only with adequate ventilation.

Local exhaust:

Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

CAS No.	Substance	Type	mg/m ³	ppm	Dust fract.
64-19-7	Acetic acid	OSHA PEL	25.0	10.0	
64-19-7	Acetic acid	ACGIH TWA		10.0	

Re Acetic acid (CAS-no. 64-19-7): STEL is 15 ppm (ACGIH).

8.3 Personal protection equipment (PPE)

Respiratory protection:

A NIOSH approved air purifying respirator equipped with universal multi-contaminant multi-gas/vapor cartridges is recommended if overexposure to chemical vapors could occur.

Hand protection:

Protective gloves made of fluorinated rubber

Eye protection:

Safety glasses with side shields or chemical safety goggles.

Other protective clothing or equipment:

protective clothing to cover exposed areas of arms, legs and torso Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Do not breathe dust/vapor/mist/gas/aerosol. Do not eat, drink or smoke when handling. Wash thoroughly after handling.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

9. Physical and chemical properties**9.1 Appearance**

Physical state : liquid
 Form : paste
 Colour : colourless
 Odour : pungent

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	not applicable	
Boiling point / boiling range	not applicable	
Flash point.....	not applicable	
Ignition temperature	ca. 460 °C (860 °F)	(-)
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Vapour pressure.....	not applicable	
Density	1.09 g/cm ³ at 20 °C (68 °F)	(DIN 53217)
Water solubility / miscibility.....	virtually insoluble	
pH-Value	not applicable	
Viscosity (dynamic)	300000 mPa.s at 25 °C (77 °F)	(DIN EN ISO 2555)

9.3 Further information

Solubility in water: Hydrolytic decomposition occurs. pH Value: Product displays acidic reaction with water.
 Explosion limits for released acetic acid: 4 - 17%(V).

Odour limit..... : no data available
 Thermal decomposition..... : No decomposition when used according to regulations.

10. Stability and reactivity**10.1 General information:**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

moisture , Heat, open flames, and other sources of ignition.

10.3 Materials to avoid

Reacts with: water , basic substances and alcohols . Reaction causes the formation of: acetic acid .

10.4 Hazardous decomposition products

By hydrolysis: acetic acid . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information**11.1 Information on toxicological effects****11.1.1 Acute toxicity****Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2009 mg/kg	Rabbit	Conclusion by analogy

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

11.1.2 Skin corrosion/irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	in vitro assay; Bovine eye / bovine cornea	Conclusion by analogy OECD 437
not irritating	Rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Further toxicological information

Other information: In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

12. Ecological information**12.1 Toxicity****Assessment:**

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

Product details:

Result/Effect	Species/Test system	Source
ErC50: > 100 mg/l (measured)	static Desmodesmus subspicatus (72 h)	Conclusion by analogy OECD 201

12.2 Persistence and degradability**Assessment:**

Silicone content: biologically not degradable. Separation by sedimentation. The product of hydrolysis (acetic acid) is readily biodegradable.

12.3 Bioaccumulative potential**Assessment:**

Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil**Assessment:**

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

12.7 Additional information

In cross-linked state not soluble in water. Easily separable from water by filtration.

13. Disposal considerations**13.1 Product disposal****Recommendation:**

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal**Recommendation:**

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information**14.1 US DOT & CANADA TDG SURFACE**

Valuation: Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

15.1 Canadian regulations

This product has been classified according to the hazard criteria of the Hazard Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

DSL Status:

This material or its components are listed on the Canadian Domestic Substances List.

Non-DSL Chemicals:

This material does not contain any non-DSL chemicals.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan	: ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	: AICS (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.
China.....	: IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada	: DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	: PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	: TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan	: TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	: REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea)	: AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by the latter.

16. Other information

16.1 Additional information:

This product has been classified according to the hazard criteria of the Hazard Products Regulations (HPR) and the SDS contains all of the information required by the HPR. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

Safety Data Sheet

Material: 60003730

**ELASTOSIL® E43
TRANSPARENT**

Version: 2.2 (CA)

Date of print: 08/24/2020

Date of last alteration: 11/15/2019

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

Revision number and the latest version date:

Version: 2.2 (CA); Date of last alteration: 11/15/2019

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists

DOT - Department of Transportation

hPa - Hectopascals

mPa*s - Milli Pascal-Seconds

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

ppm - Parts per Million

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods

ASTM D56.....

ASTM D92, DIN 51376, ISO 2592

ASTM D93, DIN 51758, ISO 2719

ASTM D3278, DIN 55680, ISO 3679

DIN 51755.....

Common name

Tagliabue (Tag) closed cup

Cleveland open cup

Pensky-Martens closed cup

Setaflash or Rapid closed cup

Abel-Pensky closed cup

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity:.....: 1 mPa*s = 1 centipoise (cP)