

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14


Revision: 08.09.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** GC6B / GC4
 - **Article number:** 32220-3055-5
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
 - **Application of the substance / the mixture** Adhesives
 - **1.3 Details of the supplier of the safety data sheet**
 - **Supplier:**
Alfa Laval Lund AB
Box 74
SE-221 00 Lund
Sweden
+46 46 36 65 00
info.se@alfalaval.com
 - **Further information obtainable from:**
For further questions regarding the safety data sheet, please contact your local Alfa Laval Sales Company which you find at www.alfalaval.com or in section 16 "Other Information" in the end of the safety data sheet
 - **1.4 Emergency telephone number:**
For immediate, life-threatening emergencies, call 999
For health advice and information (24h) dial 111 (NHS direct).
- In Europe: Call 112 and ask for poison information.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Self-heat. 1	H251	Self-heating: may catch fire.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS09
- **Signal word** Danger
- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 1)

Hazard statements

- H251 Self-heating: may catch fire.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

- P280 Wear protective clothing / face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains 25 % of components with unknown hazards to the aquatic environment.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description:

Non-volatile amide (hydrazide)

Dangerous components:

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	50-100%
NLP: 500-033-5	Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
Reg.nr.: 01-2119456619-26		
CAS: 112945-52-5	Amorphous silica, crystalline free, synthetic substance with a Community workplace exposure limit	2.5-10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information:

Immediately remove any clothing soiled by the product.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

After inhalation:

Supply fresh air.
Seek medical treatment if symptoms persists.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 2)

- **After eye contact:**
Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If symptoms persist consult doctor.
- **After swallowing:**
Rinse the mouth with water.
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** Refer to section 11.1
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water spray
Foam
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Not applicable.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Hydrogen chloride (HCl)
Carbon monoxide and carbon dioxide
Aldehyde
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Formation of toxic gases is possible during heating or in case of fire.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Absorb liquid components with liquid-binding material.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
In case of seepage into the ground inform responsible authorities.
Send for recovery or disposal in suitable receptacles.
- **6.3 Methods and material for containment and cleaning up:** Pick up mechanically.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Do not breathe vapour.

Avoid contact with skin and eyes.

Handle and open container with care.

Avoid release to the environment.

This material and its container must be disposed of in a safe way.

See Section 8 for information on personal protection equipment.

· **Information about fire - and explosion protection:** Substance/product is self ignitable.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Keep away from heat and direct sunlight.

Store in a cool location.

· **Information about storage in one common storage facility:** Store away from amines

· **Further information about storage conditions:** Keep container tightly sealed.

· **7.3 Specific end use(s)**

Adhesives

Only for trade users / technical specialists

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 112945-52-5 Amorphous silica, crystalline free, synthetic

CONTROL PARAMETERS (TWA)	Short-term value: 6 mg/m ³
	Long-term value: 2.4 mg/m ³
	Silica, amorphous

· **DNELs**

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Hazard via inhalation route: Long time exposure: 12.25 mg/m³; Acute/short term exposure: 12.25 mg/m³. Repeated dose toxicity. Overall assessment factor: 12. Dose descriptor starting point: NOAEC.

· **PNECs**

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Aqua (freshwater): 0.006 mg/L, Assessment factor: 50, Extrapolation method: Assessment factor.

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Ensure that washing facilities are available at the work place.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 4)

Avoid contact with the eyes and skin.
Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Filter P2

Filter P3

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

polymer laminate

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Limitation and supervision of exposure into the environment**

Do not allow to enter sewers/ surface or ground water.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Highly viscous

Colour: Light beige

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not applicable.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· **Flash point:** >107 °C

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 5)

· Flammability (solid, gas):	Self-heating: may catch fire.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Not determined.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Oxidising properties	Not applicable.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.24 g/cm ³
· Relative density	Not determined.
· Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Slightly soluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	60,000 mPas (Brookfield)
	Not applicable.
Kinematic:	Not applicable.
	Not determined.
· 9.2 Other information	Lowest storage temperature: -18°C Highest storage temperature: 4°C

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further data; see item 7.
- **10.2 Chemical stability**
Stable under normal temperature conditions and under recommended usage and storage.
- **Thermal decomposition / conditions to be avoided:** Exothermic thermal decomposition.
- **10.3 Possibility of hazardous reactions**
Exothermic polymerisation.
130°C
- **10.4 Conditions to avoid**
Keep away from heat.
Keep away from sources of ignition - No smoking.
Avoid hardening of large quantities in order to prevent premature reaction (exotherm) with high heat and smoke.
- **10.5 Incompatible materials:**
Reacts with amines.
Keep away from acids.
- **10.6 Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide
Aldehyde

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 6)

Hydrogen chloride (HCl)
No further data; see item 7.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Oral	NOAEL	750 mg/kg (Rat) (2 generations) 750 mg/kg/day
------	-------	--

Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700:

LD50: 13600 mg/kg, Oral Rat.

LD50: >1200 mg/kg, Dermal Rat.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Dermal	LD50	>1,600 mg/kg (Rat)
--------	------	--------------------

· Primary irritant effect:

· Skin corrosion/irritation

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Irritation of skin	Skin Corrosion/Irritation	4 (Rabbit) (OECD Guideline 404) OECD Guideline 404 (Acute Dermal Irritation / Corrosion) Result: Slightly irritating.
--------------------	---------------------------	---

Causes skin irritation.

· Serious eye damage/irritation

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Irritation of eyes	Serious Eye Damage/Irritation	(Rabbit) (OECD Guideline 405) OECD Guideline 405 (Acute Eye Irritation / Corrosion) Result: Not irritating.
--------------------	-------------------------------	---

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

· **Repeated dose toxicity** Sensitising effect by skin contact is possible by prolonged exposure.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 7)

- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

LC50 (96 h)	1.75 mg/L (Fish) (OECD Guideline 203) OECD Guideline 203 (Fish, Acute Toxicity Test), Oncorhynchus mykiss, 96 h.
EC50	220 mg/L (Algae) Chlorophyta
EC50	1.1-3.6 mg/L (Daphnia) Daphnia magna

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential**

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Bioaccumulation factor <42 (No information available)

- **12.4 Mobility in soil** Contact your supplier for more information.

- **Ecotoxicological effects:**

- **Remark:**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 8)

08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, IMDG, IATA**

UN3088

· **14.2 UN proper shipping name**
· **ADR**

3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE). ENVIRONMENTALLY HAZARDOUS

· **IMDG**

SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE), MARINE POLLUTANT

· **IATA**

SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG**



· **Class**

4.2 Substances liable to spontaneous combustion.

· **Label**

4.2

· **IATA**



· **Class**

4.2 Substances liable to spontaneous combustion.

· **Label**

4.2

· **14.4 Packing group**

· **ADR, IMDG, IATA**

II

· **14.5 Environmental hazards:**

The product contains substance which is dangerous to the environment.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 9)

· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Substances liable to spontaneous combustion.
· Hazard identification number (Kemler code):	40
· EMS Number:	F-A,S-J
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	0
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	0
· UN "Model Regulation":	UN 3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE), 4.2, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) no.1907/2006 (REACH)
EU regulation (EC) no 1272/2008 (CLP)
EC DIRECTIVE 2008/98/EC (waste)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category E2** Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling,

(Contd. on page 11)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 10)

storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for further questions.

Relevant phrases

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Alfa Laval Corporate Standards & Regulatory Operations**Contact:**

- Argentina: alfa.consulta@alfalaval.com
- Australia: australia.info@alfalaval.com
- Austria: info.mideurope@alfalaval.com
- Belgium: benelux.info@alfalaval.com
- Bolivia: alfa.consulta@alfalaval.com
- Brazil: alfalaval.br@alfalaval.com
- Bulgaria: bulgaria.info@alfalaval.com
- Canada: alfacan.info@alfalaval.com
- Chile: chile.informacion@alfalaval.com
- China: china.info@alfalaval.com
- Colombia: info.colombia@alfalaval.com
- Croatia: hrvatska.info@alfalaval.com
- Czech Republic: czechrepublic.info@alfalaval.com
- Denmark: info.nordic.dk@alfalaval.com
- Egypt: alme.marketing@alfalaval.com
- Estonia: estonia.info@alfalaval.com
- Finland: info.fi@alfalaval.com
- France: environnement@alfalaval.com
- Germany: info.mideurope@alfalaval.com
- Greece: greece.info@alfalaval.com
- Hungary: info.hu@alfalaval.com
- India: india.info@alfalaval.com
- Indonesia: alfalindo@alfalaval.com
- Israel: israel.info@alfalaval.com
- Italy: alfalaval.italia@alfalaval.com
- Latvia: latvia.info@alfalaval.com
- Lithuania: lithuania.info@alfalaval.com
- Malaysia: malaysia.info@alfalaval.com
- Mexico: mexico.info@alfalaval.com
- The Netherlands: benelux.info@alfalaval.com
- New Zealand: newzealand.info@alfalaval.com
- Norway: info.no@alfalaval.com
- Peru: ventas.peru@alfalaval.com
- Philippines: philippines.info@alfalaval.com
- Poland: poland.info@alfalaval.com
- Portugal: portugal.info@alfalaval.com
- Qatar: alme.marketing@alfalaval.com

(Contd. on page 12)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.09.2020

Version number 14

Revision: 08.09.2020

Trade name: GC6B / GC4

(Contd. of page 11)

Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com
Slovenia: slovenija.info@alfalaval.com
South Africa: info.sa@alfalaval.com
Spain: info.spain@alfalaval.com
Sweden: info.se@alfalaval.com
Switzerland: info.mideurope@alfalaval.com
Taiwan: taiwan.info@alfalaval.com
Thailand: thailand.info@alfalaval.com
Turkey: turkey@alfalaval.com
Ukraine: ukraine.info@alfalaval.com
United Arab Emirates: alme.marketing@alfalaval.com
United Kingdom: general.uk@alfalaval.com
United States: customerservice.usa@alfalaval.com
Venezuela: venezuela.info@alfalaval.com
Vietnam: vietnam.info@alfalaval.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Self-heat. 1: Self-heating substances and mixtures – Category 1
Acute Tox. 4: Acute toxicity - dermal – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* **Data compared to the previous version altered.**

GB