

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022


SECTION 1: Identification of the substance or mixture and of the supplier

- **1.1 Product identifier**
- **Trade name: GC6B / GC4**
- **Article number: 32220-3055-5**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesives
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**
Alfa Laval Technologies AB
SE-221 00 Lund
Sweden
+46 46 36 65 00
info.se@alfalaval.com

New Zealand Supplier:
Alfa Laval New Zealand Ltd
PO Box 20424, Te Rapa - Hamilton, - New Zealand
Visit: 307 Sandwich Road - Te Rapa, Hamilton, - New Zealand
Tel switchboard: +64 7 849 6025 - Fax switchboard: +64 7 849 46 19
http://www.alfalaval.co.nz - newzealand.info@alfalaval.com
- **Further information obtainable from:**
For further questions regarding the safety data sheet, please contact your local Alfa Laval Sales Company which you find at www.alfalaval.com or in section 16 "Other Information" in the end of the safety data sheet
- **1.4 Emergency telephone number:**
New Zealand:
Emergency service number: 111
National poisons centre phone: 0800 764 766.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Self-heat. 1	H251 Self-heating: may catch fire.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07 GHS09
- **Signal word** Danger

(Contd. on page 2)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 1)

- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
- **Hazard statements**
H251 Self-heating: may catch fire.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P280 Wear protective clothing / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
Contains 25 % of components with unknown hazards to the aquatic environment.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** The product is not, nor contains, a substance that is, PBT.
- **vPvB:** The product is not, nor contains a substance that is, vPvB.

SECTION 3: Composition/Information on ingredients

· 3.2 Mixtures

· Description:

	Non-volatile amide (hydrazide)	
CAS: 112945-52-5	Amorphous silica, crystalline free, synthetic	2.5-10%

· Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) Aquatic Chronic 2, H411; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C \geq 5 % Skin Irrit. 2; H315: C \geq 5 %	50-100%
-----------------------------------	---	---------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· After inhalation:

Supply fresh air.
Seek medical treatment if symptoms persists.

(Contd. on page 3)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 2)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If symptoms persist consult a doctor.
- **After swallowing:**
Rinse the mouth with water.
If symptoms persist consult a doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Fire fighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water spray
Foam
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Not applicable.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
In case of fire, the following can be released:
Nitrogen oxides (NO_x)
Hydrogen chloride (HCl)
Carbon monoxide and carbon dioxide
Aldehyde
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Do not inhale explosion gases or combustion gases.
Wear self-contained respiratory protective device.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Formation of toxic gases is possible during heating or in case of fire.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Absorb liquid components with liquid-binding material.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
In case of seepage into the ground inform responsible authorities.
Send for recovery or disposal in suitable receptacles.
- **6.3 Methods and material for containment and cleaning up:** Pick up mechanically.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Do not breathe vapour.

Avoid contact with skin and eyes.

Handle and open container with care.

Avoid release to the environment.

This material and its container must be disposed of in a safe way.

See Section 8 for information on personal protection equipment.

- **Information about fire - and explosion protection:** Substance/product is self ignitable.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep away from heat and direct sunlight.

Store in a cool location.

- **Information about storage in one common storage facility:** Reacts with amines.

- **Further information about storage conditions:** Keep container tightly sealed.

- **Recommended storage temperature:** -18 - 4 °C

7.3 Specific end use(s)

Adhesives

Only for trade users / technical specialists

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Hazard via inhalation route: Long time exposure: 12.25 mg/m³; Acute/short term exposure: 12.25 mg/m³. Repeated dose toxicity. Overall assessment factor: 12. Dose descriptor starting point: NOAEC.

PNECs

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700: Aqua (freshwater): 0.006 mg/L, Assessment factor: 50, Extrapolation method: Assessment factor.

- **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.

- **Individual protection measures, such as personal protective equipment**

General protective and hygienic measures:

Ensure that washing facilities are available at the work place.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use only in well-ventilated areas.

(Contd. on page 5)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 4)

In case of insufficient ventilation, wear suitable respiratory equipment.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Filter P2

Filter P3

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

polymer laminate

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Tightly sealed goggles

· **Environmental exposure controls** Do not allow to enter sewers/ surface or ground water.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Colour:	Light beige
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Self-heating: may catch fire.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>107 °C
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· pH	Not applicable.

(Contd. on page 6)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 5)

<ul style="list-style-type: none"> · Viscosity: · Kinematic viscosity Not applicable. · Dynamic at 20 °C: 60,000 mPas (Brookfield) · Solubility · water: Slightly soluble. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined. · Density and/or relative density · Density at 20 °C: 1.24 g/cm³ · Relative density Not determined. · Vapour density Not applicable. 	
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: Highly viscous · Explosive properties: Product does not present an explosion hazard. · Change in condition · Drip point: · Oxidising properties Not applicable. · Evaporation rate Not applicable. 	
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Self-heating: may catch fire. · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void 	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further data; see item 7.
- **10.2 Chemical stability**
Stable under normal temperature conditions and under recommended usage and storage.
- **Thermal decomposition / conditions to be avoided:** Exothermic thermal decomposition.

(Contd. on page 7)



Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 6)

- **10.3 Possibility of hazardous reactions**

Exothermic polymerisation.
130°C

- **10.4 Conditions to avoid**

Keep away from heat.
Keep away from sources of ignition - No smoking.
Avoid hardening of large quantities in order to prevent premature reaction (exotherm) with high heat and smoke.

- **10.5 Incompatible materials:**

Reacts with amines.
Keep away from acids.

- **10.6 Hazardous decomposition products:**

Nitrogen oxides
Carbon monoxide and carbon dioxide
Aldehyde
Hydrogen chloride (HCl)
No further data; see item 7.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity**

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Oral	NOAEL	750 mg/kg (Rat) (2 generations)
------	-------	---------------------------------

- **LD/LC50 values relevant for classification:**

25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700:
LD50: 13600 mg/kg, Oral Rat.
LD50: >1200 mg/kg, Dermal Rat.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Dermal	LD50	>1,600 mg/kg (Rat)
--------	------	--------------------

- **Skin corrosion/irritation**

Causes skin irritation.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Irritation of skin	Skin Corrosion/Irritation	4 (Rabbit) (OECD Guideline 404)
--------------------	---------------------------	---------------------------------

- **Serious eye damage/irritation**

Causes serious eye irritation.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Irritation of eyes	Serious Eye Damage/Irritation	(Rabbit) (OECD Guideline 405)
--------------------	-------------------------------	-------------------------------

- **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 7)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **Repeated dose toxicity** Sensitising effect by skin contact is possible by prolonged exposure.
- **11.2 Information on other hazards**
- **Endocrine disrupting properties**
Endocrine disrupting properties from <https://edlists.org>

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

LC50 (96 h)	1.75 mg/L (Fish) (OECD Guideline 203)
EC50	220 mg/L (Algae)
EC50	1.1-3.6 mg/L (Daphnia)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects** No further relevant information available.
- **Remark:**
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

(Contd. on page 9)

Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022




Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 8)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	<p style="text-align: right;">UN3088</p>
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	<p>3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), ENVIRONMENTALLY HAZARDOUS SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE), MARINE POLLUTANT</p> <p>SELF-HEATING SOLID, ORGANIC, N.O.S. (HYDRAZIDE)</p>
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG 	<div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p>4.2 Substances liable to spontaneous combustion.</p> <p>4.2</p>
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; justify-content: center; align-items: center;">  </div> <p>4.2 Substances liable to spontaneous combustion.</p> <p>4.2</p>
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p style="text-align: right;">II</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): 	<p>Environmentally hazardous substance, solid</p> <p>Yes</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Warning: Substances liable to spontaneous combustion.</p> <p>40</p> <p>F-A,S-J</p> <p>A</p>
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	<p>-----</p> <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Transport category <p style="text-align: right;">0 2</p>

(Contd. on page 10)



Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 9)

· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	0
· UN "Model Regulation":	UN 3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 4.2, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) no.1907/2006 (REACH)

EU regulation (EC) no 1272/2008 (CLP)

EC DIRECTIVE 2008/98/EC (waste)

· **New Zealand Inventory of Chemicals**

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
-----------------	--

CAS: 112945-52-5	Amorphous silica, crystalline free, synthetic
------------------	---

· **HSNO Approval numbers**

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	HSR003180
-----------------	--	-----------

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for further questions.

(Contd. on page 11)



Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 10)

· Relevant phrases

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

· Department issuing SDS: Alfa Laval Sustainability Environment**· Contact:**

Argentina: alfa.consulta@alfalaval.com
Australia: australia.info@alfalaval.com
Austria: info.mideurope@alfalaval.com
Belgium: benelux.info@alfalaval.com
Bolivia: alfa.consulta@alfalaval.com
Brazil: alfalaval.br@alfalaval.com
Bulgaria: bulgaria.info@alfalaval.com
Canada: alfacan.info@alfalaval.com
Chile: chile.informacion@alfalaval.com
China: china.info@alfalaval.com
Colombia: info.colombia@alfalaval.com
Croatia: hrvatska.info@alfalaval.com
Czech Republic: czechrepublic.info@alfalaval.com
Denmark: info.nordic.dk@alfalaval.com
Egypt: alme.marketing@alfalaval.com
Estonia: estonia.info@alfalaval.com
Finland: info.fi@alfalaval.com
France: environnement@alfalaval.com
Germany: info.mideurope@alfalaval.com
Greece: greece.info@alfalaval.com
Hungary: info.hu@alfalaval.com
India: india.info@alfalaval.com
Indonesia: alfalindo@alfalaval.com
Israel: israel.info@alfalaval.com
Italy: alfalaval.italia@alfalaval.com
Japan: hp.alfajp@alfalaval.com
Latvia: latvia.info@alfalaval.com
Lithuania: lithuania.info@alfalaval.com
Malaysia: malaysia.info@alfalaval.com
Mexico: mexico.info@alfalaval.com
The Netherlands: benelux.info@alfalaval.com
New Zealand: newzealand.info@alfalaval.com
Norway: info.no@alfalaval.com
Peru: ventas.peru@alfalaval.com
Philippines: philippines.info@alfalaval.com
Poland: poland.info@alfalaval.com
Portugal: portugal.info@alfalaval.com
Qatar: alme.marketing@alfalaval.com
Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com
Slovenia: slovenija.info@alfalaval.com
South Africa: info.sa@alfalaval.com

(Contd. on page 12)



Safety Data Sheet in accordance with HSNO

Printing date 18.02.2022

Version number 15

Revision: 18.02.2022

Trade name: GC6B / GC4

(Contd. of page 11)

Spain: info.spain@alfalaval.com
Sweden: info.se@alfalaval.com
Switzerland: info.mideurope@alfalaval.com
Taiwan: taiwan.info@alfalaval.com
Thailand: thailand.info@alfalaval.com
Turkey: turkey@alfalaval.com
Ukraine: ukraine.info@alfalaval.com
United Arab Emirates: alme.marketing@alfalaval.com
United Kingdom: general.uk@alfalaval.com
United States: customerservice.usa@alfalaval.com
Venezuela: venezuela.info@alfalaval.com
Vietnam: vietnam.info@alfalaval.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Self-heat. 1: Self-heating substances and mixtures – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* **Data compared to the previous version altered.**

-NZ-