

Page 1/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

1 Identification

· Product identifier

· Trade name: GC6C

· Article number: 3222030556

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Adhesive

· Details of the supplier of the safety data sheet

· Supplier:

Alfa Laval Technologies AB

SE-221 00 Lund

Sweden

+46 46 36 65 00

info.se@alfalaval.com

Australian supplier:

Alfa Laval Australia Pty Ltd

Locked Bag 40, Blacktown Business Centre

NSW - NSW-2148 Blacktown

Australia

Visit: 14 Healey Circuit, - NSW - NSW-2148 Huntingwood

Tel switchboard: +61 2 8822 2700 - Fax switchboard: +61 2 8822 2799

www.alfalaval.com.au australia.info@alfalaval.com

· Further information obtainable from:

For further questions regarding the safety data sheet, please contact your local Alfa Laval Sales Company which you find at www.alfalaval.com or in section 16 "Other Information" in the end of the safety data sheet

Emergency telephone number:

In Europe: Call 112 and ask for poison information Australian Poisons Information Centre Tel:13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 2)



Page 2/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 1)

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with phenol

toluene

phenol

formaldehyde

· Hazard statements

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Other hazards

· Results of PBT and vPvB assessment

- · PBT: The product is not, nor contains, a substance that is, PBT.
- · **vPvB:** The product is not, nor contains a substance that is, vPvB.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

•	· Dangerous components:			
	CAS: 9003-35-4 formaldehyde, oligomeric reaction products with phenol		25-<50%	
		Skin Sens. 1, H317		
	CAS: 64-17-5	ethanol	20-<30%	
		Flam. Liq. 2, H225; Eye Irrit. 2A, H319		
	CAS: 108-88-3	toluene	10-<20%	
		Flam. Liq. 2, H225; Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336		
	CAS: 108-95-2	phenol	3-<5%	
		Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Muta. 2, H341; STOT RE 2, H373; Skin Corr. 1B, H314		

(Contd. on page 3)



Page 3/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

	(Co	ntd. of page 2)
CAS: 67-56-1	methanol	1-<3%
	Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370	
CAS: 50-00-0	formaldehyde Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Muta. 2, H341; Carc. 1B, H350; Skin Corr. 1B, H314; Skin Sens. 1, H317; Flam. Liq. 4, H227	0.25-<1%

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult a doctor.

After eye contact:

Get medical advice/attention.

Rinse opened eye for several minutes under running water and consult a doctor.

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- · After swallowing: If symptoms persist consult a doctor.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- Extinguishing media
- · Suitable extinguishing agents:

Carbon dioxide

Sand

Fire-extinguishing powder

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Mouth respiratory protective device.

(Contd. on page 4)



Page 4/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

· Additional information

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with higher concentration.

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Do not breathe vapour.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Send for recovery or disposal in suitable receptacles.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

· Handling:

· Precautions for safe handling

Eye wash bottle or emergency eye wash fountain must be found in the work place.

See Section 8 for information on personal protection equipment.

Keep ignition sources away - Do not smoke.

Keep away from heat and direct sunlight.

Do not breathe vapour.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

When using do not eat, drink or smoke.

Use only non-sparking tools.

Information about fire - and explosion protection:

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with higher concentration.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Highly flammable.

(Contd. on page 5)



Page 5/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in well-ventilated place.

Keep container tightly closed.

Store in a cool location.

- · Information about storage in one common storage facility: See section 10 in the SDS
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Professional use only.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

CAS:	64-17-5 ethanol
WES	Long-term value: 1880 mg/m³, 1000 ppm
CAS:	108-88-3 toluene
WES	Short-term value: 574 mg/m³, 150 ppm Long-term value: 191 mg/m³, 50 ppm Sk
CAS:	108-95-2 phenol
WES	Long-term value: 4 mg/m³, 1 ppm Sk
CAS:	67-56-1 methanol
WES	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Sk
CAS:	50-00-0 formaldehyde
WES	Short-term value: 2.5 mg/m³, 2 ppm Long-term value: 1.2 mg/m³, 1 ppm Sen
DNEL	

Sen				
·DNELs				
CAS: 108-	-88-3 toluene			
Oral	DNEL - Long term, Systemic effects	8.13 mg/kg bw/day (Consumer)		
Dermal	DNEL - Long term, Systemic effects	384 mg/kg bw/day (Worker)		
Inhalative	DNEL - Long term, Systemic effects	192 mg/m3 (Worker)		
CAS: 108-	-95-2 phenol			
Oral	DNEL - Long term, Systemic effects	0.4 mg/kg bw/day (Consumer)		
Dermal	DNEL - Long term, Systemic effects	1.23 mg/kg bw/day (Worker)		
Inhalative	DNEL - Long term, Systemic effects	8 mg/m3 (Worker)		
CAS: 67-56-1 methanol				
Oral	DNEL - Long term, Systemic effects	8 mg/kg bw/day (Consumer)		
		•	(Contd. on page 6)	

— AU



Page 6/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

			(Contd. of page 5)
Dermal	DNEL - Long term, Systemic effects	40 mg/kg bw/day (Worker)	
Inhalative	DNEL - Long term, Systemic effects	260 mg/m3 (Worker)	
· PNECs			
CAS: 108	3-88-3 toluene		
PNEC 0.	68 mg/L (Freshwater)		
CAS: 108	3-95-2 phenol		
PNEC 0.	0077 mg/L (Freshwater)		
CAS: 67-	56-1 methanol		
PNEC 15	54 mg/L (Freshwater)		

- · **Additional information:** The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Eye wash bottle or emergency eye wash fontain must be found in the work place

Use only in well-ventilated areas.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Ethyl Vinyl Alcohol Laminate (EVAL)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

EVAL: >8h

NBR: 10 -480 min

(Contd. on page 7)



Page 7/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

· Eye protection:

(Contd. of page 6)



Tightly sealed goggles

· Body protection:



Protective work clothing

• Limitation and supervision of exposure into the environment Do not allow to enter sewers/ surface or ground water.

9 Physical	and	Chemical	Properties
------------	-----	----------	-------------------

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Colour:
Brown
Characteristic
Odour threshold:
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** >125 °C

• Flash point: >1 °C (ISO 2719, CLOSED CUP)

• Decomposition temperature: >200 C

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

Not determined.

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:

Upper:
Oxidising properties
Not applicable.

Vapour pressure:
Not determined.

Density at 20 °C:
1 g/cm³
Not determined.

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 8)



Page 8/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

Viscosity:

 Dynamic:
 Kinematic:
 Solvent content:
 Organic solvents:
 Other information

 Viscosity:
 1500 -3000 mPa s (25 C)
 Not determined.
 Not determined.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Chemical stability The material is stable under recommended storage and handling conditions.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· Possibility of hazardous reactions

Forms explosive gas mixture with air.

No further data; see item 7.

- · Conditions to avoid High temperature
- Incompatible materials:

Do not store together with alkalis (caustic solutions).

Reacts with strong oxidising agents.

Hazardous decomposition products:

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Poisonous gases/vapours

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity			
CAS: 108-95-2 phenol			
Dermal LD	Lo 630 mg	g/kg (Rabbit) (LD50)	
· LD/LC50 v	alues relev	vant for classification:	
CAS: 64-1	7-5 ethano	I	
Oral	LD50	7,060 mg/kg (Rat)	
Inhalative	LC50 (4 h)	20,000 mg/L (Rat)	
CAS: 108-88-3 toluene			
Oral	LD50	5,000 mg/kg (Rat)	
Dermal	LD50	12,124 mg/kg (Rabbit)	
Inhalative	LC50 (4 h)	5,320 mg/L (Mouse)	
CAS: 108-95-2 phenol			
Oral	LD50	317 mg/kg (Rat)	
Dermal	LD50	850 mg/kg (Rabbit)	
•		(Contd. on page	e 9)



Page 9/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

		(Contd. of page 8)	
CAS: 67-5	6-1 methar	nol	
Oral	LD50	5,628 mg/kg (Rat)	
Dermal	LD50	15,800 mg/kg (Rabbit)	
CAS: 50-0	CAS: 50-00-0 formaldehyde		
Oral	LD50	>200 mg/kg (Rat)	
Dermal	LD50	270 mg/kg (Rabbit)	
Inhalative	LC50 (4 h)	470 mg/L (Rat)	

· Primary irritant effect:

Skin corrosion/irritation

Causes severe skin burns and eye damage.

CAS: 67-56-1 methanol	
Irritation of skin Skin Corrosion/Irritation	(Rabbit)

Serious eye damage/irritation

Strong irritant with the danger of severe eye injury. Irritating effect.

- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Muta. 2, Carc. 1B, Repr. 1A

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 108-88-3 toluene	
LC50 (48 h)	5.5 mg/L (Fish)
NOEC - No observed effect concentration	0.74 mg/l (Daphnia)
CAS: 108-95-2 phenol	
LC50 (48 h)	8.9 mg/L (Trout)
	0.00175-67.5 mg/L (Fish) (96 h.)
EC50 (48 h) (static)	3.1 mg/L (Daphnia)
NOEC - No observed effect concentration	0.077 mg/l
CAS: 67-56-1 methanol	
EC50 (static)	>10,000 mg/L (Daphnia)
CAS: 50-00-0 formaldehyde	
LC50 (48 h) (static)	6.7 mg/L (No information available)
EC50 (static)	5.8 mg/L (Daphnia)
	(Contd. on page 10

- AU



Page 10/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 9)

CAS: 108-88-3 toluene

Biodegradability 81 % (No information available)

CAS: 108-95-2 phenol

Biodegradability 62 %

CAS: 67-56-1 methanol

Biodegradability 69-97 % (No information available)

CAS: 50-00-0 formaldehyde

Biodegradability 100 % (No information available)

Behaviour in environmental systems:

· Bioaccumulative potential

CAS: 67-56-1 methanol

Bioconcentration factor <10 (Fish)

- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · **PBT:** The product is not, nor contains, a substance that is, PBT.
- **vPvB:** The product is not, nor contains a substance that is, vPvB.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Hand over to hazardous waste disposers.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· ADG, IMDG, IATA

UN1866

· UN proper shipping name

· ADG

1866 RESIN SOLUTION

· IMDG, IATA

RESIN SOLUTION

- · Transport hazard class(es)
- · ADG, IMDG, IATA



Class 3 Flammable liquids.

(Contd. on page 11)



Page 11/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

	(Contd. of page 1
Label	3
· Packing group · ADG, IMDG, IATA	II
· Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
Transport category Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals		
All ingredients are listed.		
· Standard for the Uniform Scheduling of Medicines and Poisons		
CAS: 108-88-3	toluene	S6
CAS: 108-95-2	phenol	S2, S4, S5, S6
CAS: 67-56-1	methanol	S5, S6
CAS: 50-00-0	formaldehyde	S2, S6, S10
· Australia: Priority Existing Chemicals		
CAS: 50-00-0 formaldehyde		

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

(Contd. on page 12)



Page 12/15

Safety Data Sheet according to WHS Regulations

Version number 3 Revision: 21.02.2022 Printing date 21.02.2022

Trade name: GC6C

(Contd. of page 11)

Hazard pictograms









Signal word Danger

· Hazard-determining components of labelling:

formaldehyde, oligomeric reaction products with phenol

toluene

phenol

formaldehyde

· Hazard statements

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

Specific treatment (see on this label). P321

Take off contaminated clothing and wash it before reuse. P362+P364

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product (Contd. on page 13)



Page 13/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 12)

must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for further questions.

www.alfalaval.com

Relevant phrases

H225 Highly flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

· Department issuing SDS: Alfa Laval Sustainability Environment

Contact:

Argentina: alfa.consulta@alfalaval.com Australia: australia.info@alfalaval.com Austria: info.mideurope@alfalaval.com Belgium: benelux.info@alfalaval.com Bolivia: alfa.consulta@alfalaval.com Brazil: alfalaval.br@alfalaval.com Bulgaria: bulgaria.info@alfalaval.com Canada: alfacan.info@alfalaval.com Chile: chile.informacion@alfalaval.com China: china.info@alfalaval.com

Colombia: info.colombia@alfalaval.com Croatia: hrvatska.info@alfalaval.com

Czech Republic: czechrepublic.info@alfalaval.com

Denmark: info.nordic.dk@alfalaval.com Egypt: alme.marketing@alfalaval.com Estonia: estonia.info@alfalaval.com Finland: info.fi@alfalaval.com

France: environnement@alfalaval.com Germany: info.mideurope@alfalaval.com Greece: greece.info@alfalaval.com Hungary: info.hu@alfalaval.com India: india.info@alfalaval.com Indonesia: alfalindo@alfalaval.com

Israel: israel.info@alfalaval.com

(Contd. on page 14)



Page 14/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 13)

Italy: alfalaval.italia@alfalaval.com
Japan: hp.alfajp@alfalaval.com
Latvia: latvia.info@alfalaval.com
Lithuania: lithuania.info@alfalaval.com
Malaysia: malaysia.info@alfalaval.com
Mexico: mexico.info@alfalaval.com

The Netherlands: benelux.info@alfalaval.com New Zealand: newzealand.info@alfalaval.com

Norway: info.no@alfalaval.com Peru: ventas.peru@alfalaval.com

Philippines: philippines.info@alfalaval.com
Poland: poland.info@alfalaval.com
Portugal: portugal.info@alfalaval.com
Qatar: alme.marketing@alfalaval.com
Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com

Slovenia: slovenija.info@alfalaval.com South Africa: info.sa@alfalaval.com Spain: info.spain@alfalaval.com Sweden: info.se@alfalaval.com

Switzerland: info.mideurope@alfalaval.com

Taiwan: taiwan.info@alfalaval.com Thailand: thailand.info@alfalaval.com Turkey: turkey@alfalaval.com Ukraine: ukraine.info@alfalaval.com

United Arab Emirates: alme.marketing@alfalaval.com

United Kingdom: general.uk@alfalaval.com

United States: customerservice.usa@alfalaval.com

Venezuela: venezuela.info@alfalaval.com Vietnam: vietnam.info@alfalaval.com

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Carc. 1B: Carcinogenicity – Category 1B Repr. 1A: Reproductive toxicity – Category 1A

Repr. 1A: Reproductive toxicity – Category 1A STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

(Contd. on page 15)



Page 15/15

Safety Data Sheet according to WHS Regulations

Printing date 21.02.2022 Version number 3 Revision: 21.02.2022

Trade name: GC6C

(Contd. of page 14)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.