

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1



Reviewed on 06/13/2016

1 Identification

- **Product identifier**
- **Trade name: GC6B / GC4**
- **Application of the substance / the mixture** Adhesives
- **Details of the supplier of the safety data sheet**
- **Supplier:**
Alfa Laval Lund AB
Box 74
SE-221 00 Lund
Sweden
+46 46 36 65 00
info.se@alfalaval.com
- **Information department:**
For additional questions regarding safety data sheets please contact your local Alfa Laval Sales Company which you find on www.alfalaval.com or in safety data sheet under section 16: Other Informaion
- **Emergency telephone number:** US and Canada: 911

2 Hazard(s) identification

- **Classification of the substance or mixture**
Self-heat. 1 H251 Self-heating: may catch fire.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**


 GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labeling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
- **Hazard statements**
H251 Self-heating: may catch fire.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- **Precautionary statements**
P280 Wear protective gloves.
P273 Avoid release to the environment.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

- (Contd. of page 1)
- P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.
 P407 Maintain air gap between stacks/pallets.
- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:**

	Non-volatile amide (hydrazide)	25-50%
CAS: 112945-52-5	Amorphous silica, crystalline free, synthetic	2.5-<10%

- **Dangerous components:**

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	50-100%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.
 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

- **After inhalation:**

Supply fresh air.
 Seek medical treatment in case of complaints.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

- **After eye contact:**

IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If symptoms persist consult doctor.

- **After swallowing:**

Wash the mouth with water.
 If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** Refer to section 11.1

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

Water spray

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 2)

Foam

Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** Not applicable.

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

In case of fire, the following can be released:

Nitrogen oxides (NO_x)

Hydrogen chloride (HCl)

Carbon monoxide and carbon dioxide

Aldehyde

- **Advice for firefighters**

- **Protective equipment:**

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

- **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Formation of toxic gases is possible during heating or in case of fire.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Absorb liquid components with liquid-binding material.

Keep away from ignition sources

- **Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

In case of seepage into the ground inform responsible authorities.

Send for recovery or disposal in suitable receptacles.

- **Methods and material for containment and cleaning up:** Pick up mechanically.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Do not breathe vapour.

Avoid contact with skin and eyes.

Handle and open container with care.

Avoid release to the environment.

This material and its container must be disposed of in a safe way.

See Section 8 for information on personal protection equipment.

- **Information about protection against explosions and fires:** Substance/product is self ignitable.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Keep away from heat and direct sunlight.

Store in a cool location.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 3)

- **Information about storage in one common storage facility:** Store away from amines
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)**
Adhesives
Only for trade users / technical specialists

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Ensure that washing facilities are available at the work place.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
- **Breathing equipment:**
Not necessary if room is well-ventilated.
Filter P2
Filter P3
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
Polymere laminate
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Highly viscous

Color: Light beige

· Odor: Characteristic

· Odor threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· Flash point: > 107 °C (> 225 °F)

· Flammability (solid, gaseous): May cause fire.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Not determined.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapor pressure: Not applicable.

· Density at 20 °C (68 °F): 1.24 g/cm³ (10.348 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not applicable.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with

Water: Slightly soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 26 °C (79 °F): 30-80 Pas (Brookfield)

Kinematic: Not applicable.

Not determined.

(Contd. on page 6)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 5)

- **Solvent content:**
 - **Organic solvents:** 0.0 %
- **Other information**
 - **Lowest storage temperature:** -18 °C
 - **Highest storage temperature:** 4 °C

10 Stability and reactivity

- **Reactivity** No further data; see item 7.
- **Chemical stability**
Stable under normal temperature conditions and under recommended usage and storage.
- **Thermal decomposition / conditions to be avoided:** Exothermic thermal decomposition.
- **Possibility of hazardous reactions**
Exothermic polymerization.
130 °C
- **Conditions to avoid**
Keep away from heat.
Keep away from sources of ignition - No smoking.
Avoid hardening of large quantities in order to prevent premature reaction (exotherm) with high heat and smoke.
- **Incompatible materials:** Reacts with amines.
- **Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide
Aldehyde
Hydrogen chloride (HCl)
No further data; see item 7.

11 Toxicological information

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Irritation of skin	Skin corrosion/Irritation	4 h (rabbit) (OECD Guideline 404)
Irritation of eyes	Serious Eye Damage/Irritation	- (rabbit) (OECD Guideline 405)

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
25068-38-6 Epoxy resin system, Bisphenol-A and epichlorhydrin, reaction product, MW<700:
LD50: 13600 mg/kg, Oral Rat.
LD50: >1200 mg/kg, Dermal Rat.
- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 7)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 6)

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

EC50 | 220 mg/L (Algae)

- **Aquatic toxicity:**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

LC50 (96h) | 1.75 mg/L (Fish) (OECD Guideline 203)

EC50 | 1.1-3.6 mg/L (daphnia)

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential**

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

Bioaccumulation factor | <42 (No information available)

- **Mobility in soil** Contact your supplier for more information.

- **Ecotoxicological effects:**

- **Remark:**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016





Trade name: GC6B / GC4

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Hand over to hazardous waste disposers.
- **Uncleaned packagings:**
- **Recommendation:**
Disposal must be made according to official regulations.
Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	<p style="text-align: center;">UN3088</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · ADR · IMDG 	<p>Self-heating solid, organic, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))</p> <p>3088 Self-heating solid, organic, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), ENVIRONMENTALLY HAZARDOUS</p> <p>SELF-HEATING SOLID, ORGANIC, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="display: flex; justify-content: space-around; align-items: center;">   </div>
<ul style="list-style-type: none"> · Class · Label 	<p>4.2 Substances liable to spontaneous combustion</p> <p>4.2</p>
<ul style="list-style-type: none"> · ADR, IMDG 	<div style="display: flex; justify-content: space-around; align-items: center;">   </div>
<ul style="list-style-type: none"> · Class 	<p>4.2 Substances liable to spontaneous combustion</p>

(Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS


Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 8)

· Label	4.2
· IATA	
	
· Class	4.2 Substances liable to spontaneous combustion
· Label	4.2
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Substances liable to spontaneous combustion
· Danger code (Kemler):	40
· EMS Number:	F-A,S-J
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 15 kg On cargo aircraft only: 50 kg
· Remarks:	Special marking with the symbol (fish and tree).
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	0
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 3088 SELF-HEATING SOLID, ORGANIC, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700)), 4.2, II, ENVIRONMENTALLY HAZARDOUS

US

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) no.1907/2006 (REACH)

EU regulation (EC) no 1272/2008 (CLP)

EC DIRECTIVE 2008/98/EC (waste)

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
-----------------	---

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 10)

Hazard statements

- H251 Self-heating: may catch fire.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.

Precautionary statements

- P280 Wear protective gloves.
- P273 Avoid release to the environment.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P413 Store bulk masses greater than 1 kg at temperatures not exceeding 5°C.
- P407 Maintain air gap between stacks/pallets.

- Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

LIMITATION OF LIABILITY

This document is only intended to be used as guidance as regards the risks of which we are aware that are associated with the product. Every individual who works with the product or in close proximity of it must receive suitable training. Individuals who come into contact with the product must be capable of using their own judgement as regards conditions or methods for handling, storing and using the product. Alfa Laval is not liable for demands, losses or damage of any kind that arise from flaws or deficiencies in this document or from using, handling, storing or disposing of the product unless it can be proven that Alfa Laval has acted in a grossly negligent manner. Beyond what has been agreed upon and specified in writing with Alfa Laval in the individual case, Alfa Laval makes no promises or assumes any liability, including but not limited to implicit guarantees regarding marketability or appropriateness in terms of both the information provided in this document and the product to which the information refers.

Please contact your local Alfa Laval Sales Company for further questions:

- Department issuing SDS:** Alfa Laval Materials and Chemistry Centre (MACC)

Contact:

- Argentina: alfa.consulta@alfalaval.com
- Australia: australia.info@alfalaval.com
- Austria: info.mideurope@alfalaval.com
- Belgium: benelux.info@alfalaval.com
- Bolivia: alfa.consulta@alfalaval.com
- Brazil: alfalaval.br@alfalaval.com
- Bulgaria: bulgaria.info@alfalaval.com
- Canada: alfacan.info@alfalaval.com
- Chile: chile.informacion@alfalaval.com
- China: china.info@alfalaval.com
- Colombia: info.colombia@alfalaval.com
- Croatia: hrvatska.info@alfalaval.com
- Czech Republic: czechrepublic.info@alfalaval.com
- Denmark: info.nordic.dk@alfalaval.com
- Egypt: alme.marketing@alfalaval.com
- Estonia: estonia.info@alfalaval.com
- Finland: info.fi@alfalaval.com
- France: environnement@alfalaval.com
- Germany: info.mideurope@alfalaval.com

(Contd. on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 11)

Greece: greece.info@alfalaval.com
Hungary: info.hu@alfalaval.com
India: india.info@alfalaval.com
Indonesia: alfalindo@alfalaval.com
Israel: israel.info@alfalaval.com
Italy: alfalaval.italia@alfalaval.com
Latvia: latvia.info@alfalaval.com
Lithuania: lithuania.info@alfalaval.com
Malaysia: malaysia.info@alfalaval.com
Mexico: mexico.info@alfalaval.com
The Netherlands: benelux.info@alfalaval.com
New Zealand: newzealand.info@alfalaval.com
Norway: info.no@alfalaval.com
Peru: ventas.peru@alfalaval.com
Philippines: philippines.info@alfalaval.com
Poland: poland.info@alfalaval.com
Portugal: portugal.info@alfalaval.com
Qatar: alme.marketing@alfalaval.com
Romania: romania.info@alfalaval.com
Russia: moscow.response@alfalaval.com
Singapore: al.singapore@alfalaval.com
Slovak Republic: slovakia.info@alfalaval.com
Slovenia: slovenija.info@alfalaval.com
South Africa: info.sa@alfalaval.com
Spain: info.spain@alfalaval.com
Sweden: info.se@alfalaval.com
Switzerland: info.mideurope@alfalaval.com
Taiwan: taiwan.info@alfalaval.com
Thailand: thailand.info@alfalaval.com
Turkey: turkey@alfalaval.com
Ukraine: ukraine.info@alfalaval.com
United Arab Emirates: alme.marketing@alfalaval.com
United Kingdom: general.uk@alfalaval.com
United States: customerservice.usa@alfalaval.com
Venezuela: venezuela.info@alfalaval.com
Vietnam: vietnam.info@alfalaval.com

• **Date of preparation / last revision** 06/13/2016 / -

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Self-heat. 1: Self-Heating Substances and Mixtures, Hazard Category 1

(Contd. on page 13)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/13/2016

Version 1

Reviewed on 06/13/2016

Trade name: GC6B / GC4

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

· *** Data compared to the previous version altered.**

—US—