

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ISOFLEX TOPAS NB 52 Spray
Article-No. : 081326

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant spray
Recommended restrictions : For professional users only.
on use

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München
Geisenhausenerstr. 7
81379 München
Deutschland
Tel: +49 (0) 89 7876 0
Fax: +49 (0) 89 7876 333
info@klueber.com
E-mail address of person
responsible for the SDS : mcm@klueber.com
Material Compliance Management
National contact : Klüber Lubrication Nordic A/S
Vasagatan 36
111 20 Stockholm
Sweden
+46-8-59098600
Fax: +46-8-59098601
klueber.se@sk.klueber.com

1.4 Emergency telephone number

Emergency telephone num-
ber : 112 - ask for poison information
+49 89 7876 700 (24 hrs)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION





ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :    

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, isoalkanes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Propellant
solvent (hydrocarbons)
Synthetic hydrocarbon oil
barium complex soap

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 30 - < 50
Hydrocarbons, C7-C9, isoalkanes	921-728-3 01-2119471305-42-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	Note P	>= 25 - < 30
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.
- Risks : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. For personal protection see section 8. Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product. Do not get in eyes or mouth or on skin. Do not get on skin or clothing. Do not ingest. Do not use sparking tools. These safety instructions also apply to empty packaging which may still contain product residues. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-12-17
4.2	2020-12-17	Date of first issue: 2016-07-13	

red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C7-C9, isoalkanes	Not Assigned	NGV	30 ppm 175 mg/m ³	SE AFS (2015-11-12)
Further information	Substance can be easily absorbed through the skin.			
		KGV	60 ppm 350 mg/m ³	SE AFS (2015-11-12)
Further information	Indicative short term limit value shall be used as a recommended maximum value and should not be exceeded, Substance can be easily absorbed through the skin.			
				SE AFS (2011-12-16)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7-C9, isoalkanes	Workers	Inhalation	Long-term systemic effects	2035 mg/m ³
	Workers	Dermal	Long-term systemic effects	773 mg/kg bw/day

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only
- Filter type : Filter type A-P
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Colour : white
- Odour : characteristic
- Odour Threshold : No data available

Values refer to the propellant:

- pH : Not applicable
- Melting point/range : No data available
- Boiling point/boiling range : < -10 °C
- Flash point : -80 °C
Method: closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 11,2 %(V)
- Lower explosion limit / Lower flammability limit : 1,5 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020- 12-17
----------------	------------------------------	---	----------------------------

Vapour pressure : 2.700 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,6 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,60 g/cm³
(20 °C)

Bulk density : Not applicable

Solubility(ies)
Water solubility : < 0,1 g/l insoluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Auto-ignition temperature : > 350 °C

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : Not applicable

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Hydrocarbons, C7-C9, isoalkanes:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020- 12-17
----------------	------------------------------	---	----------------------------

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

STOT - single exposure

Components:

Hydrocarbons, C7-C9, isoalkanes:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C7-C9, isoalkanes:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 18,4 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2,4 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

aquatic invertebrates	Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0,17 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: Reproduction Test Method: OECD Test Guideline 211

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Biodegradability : Result: Not rapidly biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS (Naphtha (petroleum), light alkylate)
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADN		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
ADR		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)
RID		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1
IMDG		
Packing group	:	Not assigned by regulation
Labels	:	2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020-12-17
----------------	------------------------------	---	------------------------

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

18 Liquefied extremely flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 68,76 %

Other regulations:

Hygiene limits (AFS 2018:1), provisions - Occupational Safety and Health Administration's provisions on hygiene limits and general advice on the application of the provisions.

Young people under the age of 18 are not allowed to use or be exposed to the product profes-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE

KLÜBER
LUBRICATION

ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

sionally. Young people who will be turning 16 during the calendar year are, however, except from this rule if the product is a necessary part of their education.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Note C	:	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note P	:	The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
Note U (table 3.1)	:	When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
SE AFS	:	Sweden. Occupational Exposure Limit Values
SE AFS / NGV	:	Time Weighted Average
SE AFS / KGV	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regula-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version 4.2	Revision Date: 2020-12-17	Date of last issue: 2020-08-03 Date of first issue: 2016-07-13	Print Date: 2020- 12-17
----------------	------------------------------	---	----------------------------

tion; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relation-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - SE



ISOFLEX TOPAS NB 52 Spray

Version	Revision Date:	Date of last issue: 2020-08-03	Print Date: 2020-
4.2	2020-12-17	Date of first issue: 2016-07-13	12-17

ship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.