

Valuable heat no longer wasted

Heat recovery in a paraxylene plant, Asia

Case story

One of the major paraxylene producers in Asia replaced an existing air-cooled heat exchanger on top of a distillation column with an Alfa Laval Compabloc. The new Compabloc heat exchanger recovers 9 MW of heat. Over a year it saves the company energy valued at approximately 1.25 million euros annually. Payback time, including the installation cost, was less than 6 months.

Paraxylene production involves a series of distillation steps which use large amounts of energy. A standard 650,000 tpa plant produces approximately 170 MW of heat that is often treated as waste and cooled off. Recovering 40% of this heat leads to a 12% cut in the plant's total energy consumption.

There are typically 19 distillation columns in a paraxylene plant. Five of these produce 50% of the waste heat, making them prime candidates for an energy-recovery revamp.

New tools

The overhead vapours from these five columns are usually cooled and condensed in air-cooled heat exchangers. Due to low temperatures and engineering difficulties, heat is seldom recovered. This is too costly and technically impractical using traditional shell-and-tube technology.

Highly efficient compact heat exchangers such as the Alfa Laval Compabloc open up a range of new possibilities. The exceptionally high thermal efficiency of compact heat exchangers makes it possible to recover waste heat, even when temperatures are low and space is scarce.



Short payback time

A leading paraxylene producer in Asia operating under license from UOP exchanged two large air cooled heat exchangers for an Alfa Laval Compabloc on top of the plant's o-xylene separation column. The new heat exchanger recovers 9 MW of energy which is used for preheating boiler feedwater.

The energy recovered over a year has a value of 1.25 million euros and the revamp, including the installation cost, had a payback time of less than six months.

The compact size of the installed Compabloc made it easy to fit it into existing structures on top of the column. The unit is 0.7 by 0.7 by 1.5 metres wide and needed no extra foundation.


Perfect for heat recovery

The temperature approach in a Compabloc can be as small as 3°C (5.4°F) meaning it is very suitable for heat recovery duties.

Other possible uses of the recovered heat include heat tracing of process equipment, district heating or using the heat to run a refrigeration system.

The Compabloc was installed in 2013 and one year later, at the time of publishing this story, it is confirmed to work according to specifications.

Process overview



Replacing an existing air-cooled heat exchanger on top of a distillation column with an Alfa Laval Compabloc let the company save energy valued at approximately 1.25 million euros annually. Payback time, including the installation cost, was less than 6 months.

Fast facts



Alfa Laval Compabloc – perfect for condensing and heat recovery duties The all-welded Alfa Laval Compabloc compact heat exchanger has a solid reputation for reliability and high performance.

Superior performance

Its high turbulence and overall counter-current flow give Compabloc unrivalled thermal efficiency. It performs heat recovery duties up to five times more efficiently than traditional shell-and-tubes.

Compact size

This high efficiency makes Compablocs very compact and they can usually be installed in available spaces, for example on top of distillation columns

Low pressure drop

The short flow path and the large cross section give Compabloc a low pressure drop, making it an excellent condenser.

Minimal maintenance

Fouling is minimal in a Compabloc thanks to high turbulence. When it needs cleaning, you can either use cleaning-in-place equipment or remove the panels and clean the plates with a water jet. All channels are accessible for mechanical cleaning, meaning a Compabloc is back up to 100% performance after cleaning.

Designed and built for rough conditions Compablocs are specially developed for operating with aggressive media and are available in a wide range of corrosion resistant materials.

PPI00618EN 1408