



Notes:

- 316 SS, 18-8 Fasteners, Plastics, and Elastomers
- Weight: 14-1/2 lbs.
- Dual (Shown) and Triple Nozzle Available
- Nozzle Sizes: range from 1/4" to 1/2"
- Flow Range: 25 to 100 GPM
- Pressure Range: 20 to 1000 PSIG
- Min Full Wash Cycle: 8 minutes

		Insertion Clearance (Inches)	
		Dual	Triple
Free Hand	Clutch	4-3/4	6-3/4
	Pin	8-1/2	7-3/4
Fixed Center Line	Clutch	6-1/2	8-7/8
	Pin	9-3/4	9-3/4

UNLESS OTHERWISE SPECIFIED
 * DIMENSIONS ARE IN INCHES
 * [] DIMENSIONS ARE mm
 * DEBURR ALL SURFACES
 * FILLET RAD.: 0.015
 * TOLERANCES:
 XX ±0.01
 XXX ±0.005
 ANGLE ±1°
 MATERIAL:
 Various
 FINISH (UNLESS OTHERWISE SPECIFIED):
 ??? Ra
 SCALE: Full

Alfa Laval	
TITLE	Dual Nozzle with 2" Inlet
EQUIPMENT	GJ 8
DWG. NO.	---
	SHEET 1 OF 1

THIS DRAWING IS THE PROPERTY OF ALFA LAVAL REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

DRAWN	DATE	Rev.	Description
BFG	08/03/06	1	New Drawing