



Alfa Laval SolidC

Performance curves


SolidC-1, 50 Hz

Motor:	1500 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	160 mm
Impeller, Min. dia.:	110 mm
Pump inlet, dia.:	51 mm, DN 50
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 1.5 kW, 1410 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 160 D = 130
B = 150 E = 120
C = 140 F = 110




A = 160 D = 130
B = 150 E = 120
C = 140 F = 110

Motor:	3000 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	160 mm
Impeller, Min. dia.:	110 mm
Pump inlet, dia.:	Dia.: 51 mm, DN 50
Pump outlet, dia.:	Dia.: 38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 4 kW, 2890 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 160 D = 130
B = 150 E = 120
C = 140 F = 110



A = 160 D = 130
B = 150 E = 120
C = 140 F = 110


SolidC-1, 60 Hz

Motor:	1800 rpm. synchron.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	160 mm
Impeller, Min. dia.:	110 mm
Pump inlet, dia.:	51 mm, DN 50
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to max. motor: 1.8 kW, 1710 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 160 D = 130
B = 150 E = 120
C = 140 F = 110




A = 160 D = 130
B = 150 E = 120
C = 140 F = 110

Motor:	3600 rpm. synchron.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	160 mm
Impeller, Min. dia.:	90 mm
Pump inlet, dia.:	51 mm, DN 50
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to max. motor: 6.6 kW, 3540 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 160 D = 130 G = 100
B = 150 E = 120 H = 90
C = 140 F = 110



A = 160 D = 130 G = 100
B = 150 E = 120 H = 90
C = 140 F = 110


SolidC-2, 50 Hz

Motor:	1500 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	190 mm
Impeller, Min. dia.:	140 mm
Pump inlet, dia.:	63.5 mm, DN 65
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 1.5 kW, 1410 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140




A = 190 D = 160
B = 180 E = 150
C = 170 F = 140

Motor:	3000 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	190 mm
Impeller, Min. dia.:	140 mm
Pump inlet, dia.:	63.5 mm, DN 65
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 11 kW, 2945 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140


SolidC-2, 60Hz

Motor:	1800 rpm. synchr
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	190 mm
Impeller, Min. dia.:	140 mm
Pump inlet, dia.:	63.5 mm, DN 65
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 1.5 kW, 1710 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140




A = 190 D = 160
B = 180 E = 150
C = 170 F = 140

Motor:	3600 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	190 mm
Impeller, Min. dia.:	140 mm
Pump inlet, dia.:	63.5 mm, DN 65
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 18 kW, 3535 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140



A = 190 D = 160
B = 180 E = 150
C = 170 F = 140


SolidC-3, 50Hz

Motor:	1500 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	220 mm
Impeller, Min. dia.:	170 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 3 kW, 1420 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 220 D = 190
B = 210 E = 180
C = 200 F = 170




A = 220 D = 190
B = 210 E = 180
C = 200 F = 170

Motor:	3000 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	220 mm
Impeller, Min. dia.:	170 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 18.5 kW, 2960 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 220 D = 190
B = 210 E = 180
C = 200 F = 170



A = 220 D = 190
B = 210 E = 180
C = 200 F = 170


SolidC-3, 60Hz

Motor:	1800 rpm. synchron.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	220 mm
Impeller, Min. dia.:	170 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 3.6 kW, 1720 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 220	D = 190
B = 210	E = 180
C = 200	F = 170




A = 220	D = 190
B = 210	E = 180
C = 200	F = 170

Motor:	3600 rpm. synchron.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	220 mm
Impeller, Min. dia.:	170 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	38 mm, DN 40
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 25 kW, 3555 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 220	D = 190
B = 210	E = 180
C = 200	F = 170



A = 220	D = 190
B = 210	E = 180
C = 200	F = 170


SolidC-4, 50 Hz

Motor:	1500 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	250 mm
Impeller, Min. dia.:	200 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	51 mm, DN 50
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 4 kW, 1455 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 250 D = 220
B = 240 E = 210
C = 230 F = 200




A = 250 D = 220
B = 240 E = 210
C = 230 F = 200

Motor:	3000 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	250 mm
Impeller, Min. dia.:	200 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	51 mm, DN 50
Performance data refer to water at 20 °C	




Note! The curves refer to motor: 22 kW, 2955 rpm. asynchr., 50 Hz.

DO NOT FORGET THE SAFETY FACTOR



A = 250 D = 220
B = 240 E = 210
C = 230 F = 200



A = 250 D = 220
B = 240 E = 210
C = 230 F = 200

SolidC-4, 60 Hz

Motor:	1800 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	250 mm
Impeller, Min. dia.:	200 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	51 mm, DN 50
Performance data refer to water at 20 °C	



Note! The curves refer to motor: 6.8 kW, 1770 rpm. asynchr., 60 Hz.





DO NOT FORGET THE SAFETY FACTOR

Motor:	3600 rpm. synchr.
Tolerance:	±8% for Q ±6% for H
Impeller, Max. dia.:	250 mm
Impeller, Min. dia.:	200 mm
Pump inlet, dia.:	76 mm, DN 80
Pump outlet, dia.:	51 mm, DN 50
Performance data refer to water at 20 °C	



Note! The curves refer to motor: 25 kW, 3555 rpm. asynchr., 60 Hz.

DO NOT FORGET THE SAFETY FACTOR



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

How to contact Alfa Laval

Up-to-date Alfa Laval contact details for all countries are always available on our website at www.alfalaval.com