

Performance Curves

SolidC-2, 50 Hz

Motor: **1500 rpm. synchron.**
 Tolerance: $\pm 8\%$ for Q
 $\pm 6\%$ for H
 Impeller, Max. dia.: 190 mm
 Impeller, Min. dia.: 140 mm
 Pump inlet, Dia.: 63.5 mm, DN 65
 Pump outlet, Dia.: 38 mm, DN 40

Performance data refer to water at 20 °C.
 NOTE! The curves refer to motor: 1.5 kW, 1410 rpm. asynchr., 50 Hz.
 For smaller motors, reduce head (H) with: 3%.
 DO NOT FORGET THE SAFETY FACTOR.

Motor: **3000 rpm. synchron.**
 Tolerance: $\pm 8\%$ for Q
 $\pm 6\%$ for H
 Impeller, Max. dia.: 190 mm
 Impeller, Min. dia.: 140 mm
 Pump inlet, Dia.: 63.5 mm, DN 65
 Pump outlet, Dia.: 38 mm, DN 40

Performance data refer to water at 20 °C.
 NOTE! The curves refer to motor: 11 kW, 2945 rpm. asynchr., 50 Hz.
 For smaller motors, reduce head (H) with: 3%.
 DO NOT FORGET THE SAFETY FACTOR.

