

Alfa Laval AQ8S

Gasketed plate heat exchanger for HVAC applications

Introduction

Alfa Laval AlfaQ[™] is AHRI Certified® through the Liquid to Liquid Heat Exchangers (LLHE) Certification Program which ensures thermal performance in accordance with the product specifications.

The relatively short plate makes this model suitable for duties with short temperature programs and when a low pressure drop is appreciated. A large range of plate and gasket types is available.

Applications

• HVAC

Benefits


- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:



- Five-point alignment
- Corner guided alignment system
- Chocolate pattern distribution area
- · Glued gasket
- Clip-on gasket
- Leak chamber
- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- Lock washer
- Pressure plate roller
- Tightening bolt cover



Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, monitoring and much more.


For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.


General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

Dimensional drawing

Measurements mm (inches)





Type	Н	W	h
TS20-FM	1405 (55.3")	740 (29.1")	360 (14.2")
TS20-FG	1405 (55.3")	800 (31.5")	360 (14.2")
TS20-FS	1435 (56.5")	800 (31.5")	390 (15.4")

The number of tightening bolts may vary depending on pressure rating.

Technical data

DI-4--

Plates	туре	Free channel, mm (inches)
TS20-M	Single plate	4.0 (0.16)
Materials		
		316/316L, 254
Heat transfer plates		C-276, C-2000
		Ni, Ti, TiPd
Field gaskets		NBR, EPDM, FKM, HeatSeal
		Carbon steel
Flange connections		Metal lined: stainless steel, Alloy C-276, titanium
		Rubber lined: NBR, EPDM
Frame and pressure plate		Carbon steel, epoxy painted

Other materials may be available on request

Operational data

Frame, PV-code	Max. design pressure	Max. design
riaille, r v-code	(barg/psig)	temperature (°C/°F)
FM, pvcALS	10.0/145	180/356
FM, PED	10.0/145	210/410
FG, pvcALS	16.0/232	180/356
FG, ASME	10.3/150	177/350
FG, PED	16.0/232	180/356
FS, ASME	31.7/460	177/350
FS, PED	30.0/435	160/320

Extended pressure and temperature rating may be available on request.

Flange connections

Frame model	Connection standard
	EN 1092-1 DN200 PN10
FM, pvcALS	ASME B16.5 Class 150 NPS 8
	JIS B2220 10K 200A
FM, PED	EN 1092-1 DN200 PN10
	ASME B16.5 Class 150 NPS 8
	EN 1092-1 DN200 PN10
EC DVALC	ASME B16.5 Class 150 NPS 8
FG, pvcALS	JIS B2220 10K 200A
	JIS B2220 16K 200A
FG, ASME	ASME B16.5 Class150 NPS 8
FG, PED	EN 1092-1 DN200 PN16
	ASME B16.5 Class 150 NPS 8
FC ACME	ASME B16.5 Class 150 NPS 8
FS, ASME	ASME B16.5 Class 300 NPS 8
	EN 1092-1 DN200 PN25
FS, PED	EN 1092-1 DN200 PN40
	ASME B16.5 Class 300 NPS 8

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T 9115.

Certificates



This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE00104-4-EN-GB © Alfa Laval Corporate AB